

# Zeta 9V Stand-Alone Smoke Alarm

(SA-739/1)



Model	SA-739/1
Smoke Sensitivity	( $2.31 \pm 1.37$ )% / ft Obscuration (UL standard) 0.010 dB/m to 0.160 dB/m (VdS EN 14604)
Power supply	9V battery or 9V lithium battery
Battery life	At least 12 months under normal conditions with GP Green Cell battery
Low battery life	Up to 30 days warning signal
Alarm indicator	Continuously emitting red light
Alarm sound level	85dB at 3m
Operating Temp.	0°C to 50°C
Humidity	10% to 95%RH, no condensation or icing
Interconnection	Up to 38 units

This versatile stand-alone photoelectric residential smoke alarm is VdS approved (Germany) and can be calibrated to either UL, BSI or VdS requirements.

It features VdS and UL-approved photoelectric sensing components with precise smoke detection and a long life operation (2 years life with a 9 V common alkaline battery) or (10 years with 9 V Li battery). A proved quality with 10 million pieces installed over the world. Russian standard model available too.

## Features

- ✓ Photoelectric sensing technology.
- ✓ Easy installation and maintenance.
- ✓ Sealed Battery case of the back available (with 10-year Li Battery model)
- ✓ Sleek low-profile design.
- ✓ SMD circuit board design-satisfactory quality and reliability guaranteed.
- ✓ Low-battery warning.
- ✓ Test button
- ✓ Loud alarm signal of exceeding 85 dB in alarm mode.
- ✓ Five-year limited warranty.
- ✓ HUSH button, to stop the alarm from sounding.
- ✓ 10-year Long-life lithium battery (optional).
- ✓ The power supply will be cut out automatically when removing the detector from the base. (available for NB739-1-S, NB739-1-I-S NB739-2-S and NB739-2-I-S series).