



Wireless Optical & Heat Detector

Key Features



EN54-25 approved



868 - 870 MHz operating frequency



Powered by lithium metal batteries



Modern design



360 degree LED indication



Overview



The Wi-Fyre Wireless Optical Heat Detector consists of a ProFyre optical-heat detector head combined with the Wi-Fyre wireless base. The detector uses 'or' logic and is designed to respond to both smoke and/or heat, whichever is triggered first, and is designed and tested in accordance with EN54 parts 5 & 7.



Approvals

All Wi-Fyre Devices are fully certified to EN54-25 - the European product standard for wireless fire alarms, which necessitates third party assessment to confirm that it meets very specific requirements.

Wi-Fyre also complies with ENTSI 300:200 - the standard requirements for the Radio Equipment Directive (RED), and BS 5839-1 - the code of practise for design, installation, commissioning and maintenance of fire alarm systems in non-domestic premises.



CE 16
1008

EF-109-DoP-1

1008-CPR-MC 69251485
0001





Tech Specs

Radio

 Operating Frequency	868 - 870 MHz, 14dBm
 Range	150m open area

Detection

 Detector Class	Optical smoke and fixed heat
 Alarm Condition	2.4% obs/m
 Coverage	100m ²

Electrical

 Power Source







4 x Lithium AA Cell (Saft LS14500)

 Battery Life

Up to 3 years

Environmental

 Operating Temperature	-10 to +50°C
 Humidity	93% rH (non-condensing)
 Ingress Protection	IP21
 Design Environment	Indoor use only

Mechanical

 Housing Material

Polycarbonate and ABS

 Colour



White



Tech Specs

Size & Weight

Size



Weight

0.31kg (0.63 lbs)

Ordering Information

Part Code	Description
10-013	Wireless Optical & Heat Detector with Batteries
10-080	Wireless Detector Lithium Metal Battery Pack
10-084	Wireless Detector Base without Batteries
10-088	Wireless Optical & Heat Detector Head